



Overflow Fittings

Lightweight, yet strong and cost effective, the STÖRNCH PVC-U Solvent Weld Overflow Pipe Fittings are made for condensate removal. Manufactured from PVC-U, the solvent weld system is suitable for use in both low and high temperature environments.

Use with the STÖRNCH Overflow Pipe - GMDP1W & GMDP1B; with a significantly thicker wall than standard overflow pipe, this product is far less prone to bowing and easier to cut with secateur-style cutters. The 3/4" (21.5mm) pipe is available in White and Black to compliment the fittings and meets most installation requirements.

USES

Condensate removal

MATERIAL

Polyvinyl chloride unplasticized (PVC-U)

FEATURES

- Lightweight and strong
- Available in 21.5mm, White or Black
- Solvent weld connection
- Use GMDP35 Solvent Cement



Part Number	Description	Size	Colour	Flashpoint	Decomposition Temp	Relative Density	Qty/Pk
GMDP2W-5	Coupling	3/4" (21.5mm)	White	>350°C	>250°C	Approx. 1.0	5
GMDP2B-5	Coupling	3/4" (21.5mm)	Black	>350°C	>250°C	Approx. 1.0	5
GMDP3W-5	Elbow	3/4" (21.5mm)	White	>350°C	>250°C	Approx. 1.0	5
GMDP3B-5	Elbow	3/4" (21.5mm)	Black	>350°C	>250°C	Approx. 1.0	5
GMDP4W-5	45° Bend	3/4" (21.5mm)	White	>350°C	>250°C	Approx. 1.0	5
GMDP4B-5	45° Bend	3/4" (21.5mm)	Black	>350°C	>250°C	Approx. 1.0	5
GMDP5W-5	Equal Tee	3/4" (21.5mm)	White	>350°C	>250°C	Approx. 1.0	5
GMDP5B-5	Equal Tee	3/4" (21.5mm)	Black	>350°C	>250°C	Approx. 1.0	5

The information in this datasheet is intended for reference purposes only and may be modified at any time without prior notice or obligation. All data is provided in good faith and is accurate to the best of our knowledge at the time of release.