

# Hydron Dairy Pump



The **Dairy Case Pump** is a low profile, yet powerful, piston pump designed for use with dairy case installations. Its ultra low height also means that it can be used for dairy cases where height is a restriction. It has been designed for when low gravity drain is not available. Pumps away defrost water and filters particles with integrated mesh filter.



## TECHNICAL SPECIFICATION

|                      |                              |
|----------------------|------------------------------|
| Input Voltage:       | 230V 50Hz +/-10%             |
| Pumping Head:        | 30 metres                    |
| Max Flow Rate:       | 110ltr/hr                    |
| Tank Capacity:       | 5ltr                         |
| Ambient Temperature: | 0-50°C                       |
| Power Consumption:   | 37W                          |
| Dimensions:          | 465 x 205 x 63mm (L x W x D) |
| Inlet:               | TOP: 50mm Ø / SIDE: 38mm Ø   |
| Outlet connection:   | 15mm Ø                       |
| Built-in check valve |                              |



Made in Britain

T. 01206 864 467  
sales@greenmillac.com  
www.greenmillac.com

## FLOW RATES

| Performance |          |          |          |          |          |
|-------------|----------|----------|----------|----------|----------|
| 1m          | 10m      | 15m      | 20m      | 25m      | 30m      |
| GMP36       |          |          |          |          |          |
| 110ltr/hr   | 60ltr/hr | 50ltr/hr | 45ltr/hr | 40ltr/hr | 25ltr/hr |

PRODUCT CODE:  
**GMP36**