

# ► Rubber Support Feet

**STÖRNCH Rubber Support Feet** are a neat and tidy non-penetrative roof top support solution. The feet have 40mm x 20mm aluminium channel recessed into the top face to allow for easy fixing of services. Suitable for pipework, duct and cable tray runs. The Rubber Support Feet are made of durable, recycled rubber, which offers built-in anti-vibration and makes it both economical and environmentally responsible.

**COMPOSITION:**


The rubber is milled, sieved & graded Styrene Butadiene rubber (Black SBR) in reclaimed truck/lorry tyre shred & granular form. Bound together using a 8% ratio of moisture curing Polyurethane Pre-Polymer UV Resistant Recycled Rubber

**WORKING TEMPERATURE RANGE:**

-35°C to +80°C  
All dimensions +/- 2mm. Weight per unit +/- 3%



The T-bars are even more eco friendly as the need for adhesive to hold the channel in place has been completely eliminated



Code	Description	Height (A) mm	Width (B) mm	Length (C) mm	Max Load/ Foot (Kg)	Weight (Kg)
GMCG20	Small Rubber Support Foot	100	183	250	160	2.5
GMCG21	Medium Rubber Support Foot	100	183	400	240	4.3
GMCG22	Large Rubber Support Foot	100	225	600	450	8.1
GMCG23	Extra Large Rubber Support Foot	100	183	1000	645	11.4



100% UK Manufacture  
100% UK Sourced Materials

The information in this datasheet is intended for reference purposes only and may be modified at any time without prior notice or obligation. All data is provided in good faith and is accurate to the best of our knowledge at the time of release.

