

Condensate Removal Pipe

PRODUCT CODE(S)

GMDP10W/10B/20/20B

Lightweight, yet strong and cost effective, the ABS Waste Pipe is ideal for condensate removal. Manufactured from Acrylonitrile-butadiene-styrene (ABS), the solvent weld system is suitable for use in both low and high temperature environments.

The 1-1/4" (32mm) pipe is available in White and Black, with the 1-1/2" (40mm) available in white only. A range of fittings is available to compliment this pipe and meet most installation requirements.



Code	GMDP10W	GMDP10B	GMDP20	GMDP20B
Size	1-1/4" (32mm)	1-1/4" (32mm)	1-1/2" (40mm)	1-1/2" (40mm)
Length	3m	3m	3m	3m
Colour	White	Black	White	Black
Flashpoint	>350°C	>350°C	>350°C	>350°C
Decomposition Temp.	>250°C	>250°C	>250°C	>250°C
Relative Density:	Approx. 1.0	Approx. 1.0	Approx. 1.0	Approx. 1.0

USES

Condensate removal

MATERIAL

Acrylonitrile-butadiene-styrene (ABS).

FEATURES

- Lightweight and strong
- Available in White and Black
- No expansion gap required
- Solvent weld connection
- Use GMDP35 Solvent Cement